

2.側面発光、小型・薄型

Side-lighting, compact/ thin type

Distributeur : JBG-METAFIX

Product code	Color variation	P*1 (mW)	Pd (mW)	IF (mA)	IFP	VR (V)	Top (°C)	Tst (°C)
CL-375HR/YG	Red	90	78	30	100	4	-25~+80	-30~+85
	Yellow green		65	25				
CL-375HR/SYG	Red	90	78	30	100	5	-25~+80	-30~+85
	Yellow green					4		
CL-375TD/SYG	Orange	110	78	30	100	4	-25~+80	-30~+85
	Yellow green					5		

* 1 P means total value of power dissipation when both colors are on.

(Ta 25°C)

Product code	Color variation	VF			λ_d typ (nm)	λ_p typ (nm)	I_v		
		I_F (mA)	typ (v)	max (v)			I_F (mA)	min (mcd)	typ (mcd)
CL-375HR/YG	Red	20	1.80	-	-	655	20	-	23
	Yellow green		2.20	-	570	-		-	18
CL-375HR/SYG	Red	20	1.80	2.6	-	-	20	-	23
	Yellow green		2.20	2.6	-	-		-	58
CL-375TD/SYG	Orange	20	2.10	2.6	605	-	20	16	60
	Yellow green		2.20	2.6	575	-		20	58

単位 Unit : mm

LED die (long wave length)

LED die (short wave length)

Soldering terminal

Resin

P.C. board

Cathode mark

包装数量:3,000個/1リール(Φ 180mm) Loaded quantity:3,000Pcs./1 reel (Φ180mm)